

ARCH 1130

BUILDING TECHNOLOGY I

Professor Montgomery

FALL 2012



SUBJECT

WOOD

light frame construction_part I

chapter 5

DATE

FALL 2012

PROFESSOR

MONTGOMERY



WOOD

Professor Montgomery

light frame construction

arch 1130

this week

objective:

overview of the nature of
light wood frame
construction and the
sequence and details of the
assembly of a light wood
frame structure



- ✱ transition from heavy timber
- ✱ inherent advantages

- ✱ platform vs balloon
- ✱ framing floors



HEAVY TIMBER CONSTRUCTION

Professor Montgomery

structural frame

arch 1130



HEAVY TIMBER CONSTRUCTION

Professor Montgomery

structural frame

arch 1130



HEAVY TIMBER CONSTRUCTION

Professor Montgomery

structural frame

arch 1130



HEAVY TIMBER CONSTRUCTION

Professor Montgomery

connections

arch 1130



HEAVY TIMBER CONSTRUCTION

Professor Montgomery

structural frame

arch 1130



HEAVY TIMBER CONSTRUCTION

Professor Montgomery

structural frame

arch 1130



TRANSITION

Professor Montgomery

to light wood frame construction

arch 1130



TRANSITION

Professor Montgomery

to light wood frame construction

arch 1130



WOOD


advantages of light wood construction

Professor Montgomery

arch 1130



BALLOON FRAME CONSTRUCTION



PLATFORM FRAME CONSTRUCTION


WOOD

types of light wood frame construction

Professor Montgomery

arch 1130


In framing is rarely used today, shrinkage it affords may be and stucco finishes.



BALLOON FRAME

WOOD

Professor Montgomery



PLATFORM FRAME

types of light wood frame construction

arch 1130

*PLATFORM FRAMING ADVANTAGES:

* SHORT STUD LENGTHS

* FIRESTOPPING BETWEEN
FLOORS

* WORKING SURFACE
DURING CONSTRUCTION

*PLATFORM FRAMING DISADVANTAGES:

* VERTICAL SHRINKAGE
WITH MOISTURE LOSS



WOOD

Professor Montgomery

platform frame construction

arch 1130



LIGHT WOOD FRAME CONSTRUCTION

Professor Montgomery

foundations

arch 1130




LIGHT WOOD FRAME CONSTRUCTION

Professor Montgomery

foundations

arch 1130



LIGHT WOOD FRAME CONSTRUCTION

Professor Montgomery

foundations

arch 1130




LIGHT WOOD FRAME CONSTRUCTION

Professor Montgomery

foundations

arch 1130



LIGHT WOOD FRAMING

Professor Montgomery


building the frame _floors

arch 1130

FOUNDATION WALLS 3.13

The top of a foundation wall must be prepared to receive, support, and anchor the wall and floor systems of the superstructure.


- Sill plate anchors or holdowns are required to secure the wall and floor framing to the foundation against uplifting wind or seismic forces.





Wood Joists

$\frac{1}{2}$ " (13) ϕ anchor bolts embedded at least 7" (180) into concrete or the grouted cells of masonry foundation walls at no more than 6' (1830) o.c.; minimum of two bolts per sill piece w/ one within 12" (305) of each end; more stringent requirements exist for Seismic Zones 3 and 4.

- Provide $\frac{1}{2}$ " (13) minimum air space on the tops, sides, and ends of wood beams entering a concrete or masonry wall unless pressure-treated wood is used; additional space may be required for construction access.



Wood Beams



LIGHT WOOD FRAMING

Professor Montgomery

building the frame _floors

arch 1130



LIGHT WOOD FRAMING

Professor Montgomery

building the frame _floors

arch 1130




LIGHT WOOD FRAMING

Professor Montgomery

building the frame _floors

arch 1130



Span Ranges for Wood Joists

• 2x6	up to 10' (3050)	
• 2x8	8' to 12' (2440 to 3660)	
• 2x10	10' to 14' (3050 to 4265)	
• 2x12	12' to 18' (3660 to 5485)	

- Rule of thumb for estimating joist depth: span/16
- Joist deflection should not to exceed 1/360 th of span.

LIGHT WOOD FRAMING


Professor Montgomery

building the frame _floors

arch 1130

spanning capability of the subflooring.
Cavities can accommodate piping, wiring, and thermal insulation.
Ceiling may be applied directly to joists, or be suspended to lower ceiling area or conceal mechanical runs perpendicular to joists.

- End joists may be doubled to provide additional support for perimeter wall framing.



- Lateral support required for joist ends
Rim joist or header

- Joist span; see 4.27

- Sheathing or subflooring ties and stabilizes the joists to prevent twisting and buckling; see 4.32.
- Finish flooring is laid over wood panel or plank subflooring; some finish flooring materials may require additional underlayment.

Because wood light framing is combustible, it must be protected by finish flooring and ceiling materials for its fire-resistance rating.

- The susceptibility of wood light framing to decay and insect infestation requires positive site drainage, adequate separation from the ground, appropriate use of pressure-treated lumber, and ventilation to control condensation in enclosed spaces.
- See 12.11–12.12 for discussion of wood as a construction material.



LIGHT WOOD FRAMING

Professor Montgomery

building the frame _floors

arch 1130



LIGHT WOOD FRAMING

Professor Montgomery

floor openings

arch 1130



LIGHT WOOD FRAMING

Professor Montgomery




framed walls

arch 1130

wrap up

**LIGHT WOOD FRAME CONSTRUCTION
IS BY FAR THE MOST POPULAR
FORM OF CONSTRUCTION IN THE US**



- * simple tools and techniques
- * light members
- * quickly assembled
- * from a renewable source
- * durable when protected
- * only limits are the carpenter's imagination and ability