



US006637167B2

(12) **United States Patent**  
**Hanna**

(10) **Patent No.:** **US 6,637,167 B2**  
(45) **Date of Patent:** **Oct. 28, 2003**

(54) **MODULAR WALL CONSTRUCTION**

2,208,589 A 7/1940 Leemhuis

(75) Inventor: **George Khalil Hanna, Rivervale (AU)**

3,862,737 A 1/1975 Fuston, Jr.

4,294,051 A \* 10/1981 Hughes ..... 52/98

(73) Assignee: **Strongwall International, Ltd., East Perth (AU)**

5,309,686 A 5/1994 Underwood et al.

5,368,416 A 11/1994 Cataldo

5,706,620 A 1/1998 DeZan

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

**FOREIGN PATENT DOCUMENTS**

AU	2938249	9/1950
CH	568451	10/1975
GB	2111633	7/1983

(21) Appl. No.: **10/202,926**

(22) Filed: **Jul. 25, 2002**

\* cited by examiner

(65) **Prior Publication Data**

US 2002/0174619 A1 Nov. 28, 2002

**Related U.S. Application Data**

(63) Continuation of application No. 09/486,135, filed as application No. PCT/AU98/00652 on Aug. 19, 1998, now Pat. No. 6,584,750.

*Primary Examiner*—Carl D. Friedman

*Assistant Examiner*—Naoko Slack

(74) *Attorney, Agent, or Firm*—Dorsey & Whitney LLP

(30) **Foreign Application Priority Data**

Aug. 19, 1997 (AU) ..... PO 8647

Dec. 19, 1997 (AU) ..... PP 1067

Jun. 9, 1998 (AU) ..... PP 3966

(57) **ABSTRACT**

Disclosed is a method of construction of a wall from first, second and end modules each forming part of the wall. The method includes assembly of two modules being first, end or first and end modules having portions forming part of the wall by aligning these modules in a desired alignment and connecting them together with connection means to form a supporting structure for second modules. The connection means has a tie portion generally extending in the direction of the alignment. The tie portion has a portion corresponding with connection portions of a second module and cooperation of the corresponding tie portion, extending between guides formed as part of the tie portion, with the connection portions connects the second module to the supporting structure. In such manner, a portion of a wall may be constructed. Use of mortar of scaffolding and concrete pouring techniques may thus be avoided in construction of a structure.

(51) **Int. Cl.**<sup>7</sup> ..... **E04C 5/08**

(52) **U.S. Cl.** ..... **52/223.7; 52/282.2; 52/282.4; 52/565; 52/586.1; 52/745.1**

(58) **Field of Search** ..... 52/283, 282.5, 52/223.7, 223.13, 223.14, 281, 282.2, 282.4, 285.4, 286, 562, 565, 582.1, 586.1, 586.2, 585.1, 745.1

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,553,037 A 9/1925 Fritz

**18 Claims, 31 Drawing Sheets**




Fig 1a.





Fig 1b.







Fig 3a.




Fig 3b.






Fig 4a.



C

Fig 4b.



36

Fig 5a.





Fig 5b.







Fig 7a.




Fig 7b.






Fig 8a.




Fig 8b.




Fig 8c.




Fig 9.





Fig 10.






Fig 11d.




Fig 11c.





Fig 11b.





Fig 11a.

Fig 12a.




Fig 12b.




Fig 12c.






Fig 12d.














Fig 17a.






Fig 17b.










**Fig 20b.**



**Fig 20c.**




Fig 21a.




Fig 21c.




Fig 21b.




Fig 21d.




Fig 22a.




Fig 22c.




Fig 22b.





Fig 22d.






Fig 23a.




Fig 23b.




Fig 23c.



Fig 24a.




Fig 24b.




Fig 24c.




Fig 24d.




Fig 25a.




Fig 25c.




Fig 25b.




Fig 25d.




Fig 26a.




Fig 26c.




Fig 26e.




Fig 26d.




Fig 26b.




Fig 27a.




Fig 27b.




Fig 27c.




Fig 28a.




Fig 28b.




Fig 28c.




Fig 28d.




Fig 28e.





Fig 29.






Fig 30e.




Fig 30f.




Fig 30c.





Fig 30d.







Fig 31b.




Fig 31d.




Fig 31e.




Fig 31c.



**MODULAR WALL CONSTRUCTION**

This application is a continuation of U.S. patent application Ser. No. 09/486,135, filed May 5, 2000, now U.S. Pat. No. 6,584,750, which claims the priority of PCT/AU98/00652, filed Aug. 19, 1998, which in turn claims the priority of Australian patent application numbers PO8647 filed Aug. 19, 1997, PP1067 filed Dec. 19, 1997, and PP3966 filed Jun. 9, 1998, all of which are incorporated herein by reference.

**FIELD OF THE INVENTION**

This invention relates to a system or method for the modular construction of walls of the type used in the building industry generally and in the housing industry in particular. The system or method is suitable for construction of both load and non-load bearing walls. The system is called the STRONGWALL™ construction system.

**BACKGROUND TO THE INVENTION**

Structural walls, as generally used in the building and housing industries, fall into one of the following categories, being blockwork construction; in situ concrete, or similar curing material; prefabricated panels, requiring a secondary process, such as post-tensioning, or on site bolting.

Brickwork or blockwork wall construction requires the slow, labour intensive process of mortaring each joint, maintaining strict discipline to horizontal and vertical alignments and requires scaffolding for lifts greater than 1.8 metres, increasing cost and slowing construction. This category is greatly affected by the weather.

Clad framework is also labour intensive whether the framework is fabricated from steel, timber or other material. Modern construction tools, fasteners and equipment needs to be employed. It is also greatly affected by weather conditions.

In situ concrete wall construction is similarly labour intensive, requiring teams to construct formwork, place reinforcement erect scaffolding, propping and shoring; and then pour the concrete. The forming, placing and curing time create extra costs and lengthy construction time. Any errors in the process necessitate expensive remedies and long delays and, again, the process is greatly affected by weather conditions.

Prefabricated panels relieve many of the problems associated with the previous methods, by substantially reducing time on site, and confining much of the labor intensive work of fabrication to an efficient factory environment. However, to make such a system cost effective, the panels need to be of such a scale that cranes are required in the factory and on site to move and place the panels, and methods of connection and alignment become secondary processes that add to the cost of construction.

In each of the prior art methods of construction, a high degree of direct supervision and/or a highly skilled work force is required to efficiently and safely construct a wall of acceptable quality and standard.

**SUMMARY OF THE INVENTION**

It is the object of the present invention to provide a fast and economical system or method of construction of a wall that reduces the dependency on skilled labour; cranes; modern construction tools and fasteners; and scaffolding for the construction of load bearing and non-load bearing walls.

With this object in view, the present invention provides, in a first aspect, a method of construction of a wall from first,

second and end modules each having a portion forming part of the wall including:

aligning a first or end module and one of: a first and an end module in a desired alignment;

connecting the two modules together with at least one connection means, having a tie portion generally extending in the direction of the alignment, to form a supporting structure for at least one second module;

connecting a second module to the supporting structure by cooperation of a connection portion of the second module with a corresponding connection portion of said supporting structure to form at least a portion of the wall.

In this form of the invention, first and end modules may be called supporting modules.

In a preferred embodiment of the invention, the connection portion of the second module cooperatively engages with a corresponding portion of the tie portion of the connection means. Such engagement allows connection of the second module to the supporting structure forming part of the wall and may allow, during construction, the second module to be temporarily hung from the supporting structure, which may be called a hanger unit.

The connection means may be provided with one or a number of guide means for locating the second module in a desired space relation to the supporting structure. The guide means are positioned appropriately relative to the tie portion to achieve this objective. The guide means may form part of the tie portions with the corresponding tie portions extending between them.

The first, end or first and end modules may be connected together by a plurality of connection means spaced along vertical lengths of the adjoining modules providing a plurality of corresponding different tie portions for engaging cooperation with plural connection portions of the second module allowing connection to the supporting structure. The connection means may be the same or different, for example connection means connecting first modules may be different in length than those connecting end modules; or first and end modules. Length may be dictated by flange length of adjoining modules. At least two such connection means may be used to connect adjoining modules therefore providing at least two corresponding tie portions for engagement with two second module connection portions. A greater number than two may be used as necessary.

The second modules may have a T-section with a flange portion and a vertically extending web portion provided with at least two connection portions. In this case, the corresponding tie portions may have length substantially equal the width of the web of the second module. First modules may also have a T-section with a flange portion and a web portion and may be assembled from L-shaped or other sub-first modules, for example half modules, where desired. On connection, the vertically extending web portions of second modules extend between the guide means of the connection means.

In a particularly preferred aspect of the invention, bevelled slots or cuts may be employed as second module connection portions which, during construction, engage with rods forming at least two corresponding tie portions of said connection means for connection of second modules to the supporting structure. This should enable secure connection between the second module and the supporting structure but use of further fastening is not precluded.

The wall may include a number of end modules defining the start and end of the wall. End modules may have an L-section rather than a T-section preferred for the first and

second modules and may be similar to a half section. The same wall may also have one or more starts and ends along its length. At each start and end an end module may be connected with connection means, as described above, to a first module. End modules may be connected together to form supporting structures for second modules, notably at piers in a parged wall construction.

End modules may also define openings in a wall such as doors and windows. For these cases and also in the case of the same wall abutting another wall (for example, at right angle to it) the end modules may be connected by connection means to a door or window frame or similar fitting or to another wall. Connection means may be hook bracket assemblies with co-operating portions fixed to the door or window frame and end modules at each side of the door or window frame and fixed to the end module and the abutting wall. Hook bracket assemblies on either side of the door or window frame are advantageously in inverted relation to each other to facilitate construction.

In analogous manner, internal walls or partitions may be connected to other walls or partitions of the structure with hook bracket assemblies. Thus a first wall or partition may be connected to a second wall or partition by hook bracket assemblies having first cooperating portions connected to the first wall or partition along a line of desired connection and second cooperating portions connected along a vertical length of one end of the second wall or partition such that on cooperation, connection is made. Two or three such hook bracket assemblies are generally suitable to connect one wall or partition to another.

The modules of the supporting structure, that is the first modules, end modules or the first and end modules, may be aligned in a desired alignment of the wall. For example, at a corner, two first modules may be aligned at the angle of the corner and, depending on whether an internal or external corner is to be formed, a suitably angled key or tie rod may be employed to assist in their connection. If a right angle corner is required, the two first modules are aligned at right angles such that they may be connected together. Two such modules may be connected with the assistance of a corner tie rod with two sets of guides such that on connection, the modules form a supporting structure for two second modules to complete, for example, an external corner. The first modules may form part of adjoining supporting structures. The first or second modules may have flanges or webs shortened or otherwise modified to suit the corner, particularly where an angled corner is required.

A corner, for example an internal corner, may be constructed by aligning modules of adjoining supporting structures at the angle of the corner and connecting these with the assistance of a key or tie portion angled to suit the angle of the corner. So, at a right angle corner, the corner key or corner tie rod may be shaped as a right angle.

A capping member may be used at the top or bottom of a portion of the wall for further connection of modules comprising the wall portion and distribution of horizontal and vertical forces along the wall. The capping member may be plain or a castellated member provided with cleats for connection to structural members supported on top of the wall.

In a further aspect of the invention, there is provided a kit comprising first modules, second modules, end modules, module connection means, capping members, doorframes, window frames and windows to fit the frames, and door and window connection means for use in accordance with the method of the present invention.

In a still further aspect of the invention, there is provided a structure including a wall constructed in accordance with the method of the present invention.

It will be understood that the method is not restricted to the construction of walls; and wall-like structures such as fences, partitions, piers, columns and so on may be suitably constructed with the method of the invention. Thus the term "wall" is intended herein to be compendious description of all such structures.

A parged wall may be constructed in accordance with the methods above described. In this case, the wall has at least one pier along its length including at least two end modules or a first and an end module being, pier modules connected together by first connection means to form a supporting structure for a second module of the pier. The supporting structure is connected to the remainder of the wall by a bracket having first means for engaging connection means connecting two modules forming part of the remainder of the wall together; and second means for engaging first connection means connecting the at least two pier modules together. On engagement of the first and second engagement means with the connection means the pier is connected to the remainder of the wall. Engagement may be made with tie or key portions of the connection means as appropriate. The bracket may connect with tie and key portions of the first connection means and connection means respectively, or vice versa.

In one further aspect of the invention the method is used for construction of a structural column comprising assembly and connection of second modules having a flange and a web with angled slots formed proximate the ends of said second module webs wherein webs of two second modules are aligned in opposition with slots facing downwards; downward facing cleats of a connection means are engaged with the slots at top and bottom of the webs to form a supporting structure comprised of said second modules and connection bracket; and angled slots of two further second modules facing upward are engaged with upward facing cleats of said connection means at top and bottom of said further second modules to form the column.

The column connection means may be a bracket having a body of rectangular section, two opposed sides of said section being connected to cleats being angled upward from a horizontal medial axis of said section and the remaining two opposed sides of said section being connected to cleats angled downward from the horizontal medial axis of the connection means. The cleats comprise plate portions for engaging angled slots of second modules having flange and web and formed in the web and upstanding walls defining two edges of said plate portions. These walls are provided to make engagement secure. Engagement of the cleats with the angled slots of the second modules allows construction of a column.

The connection means may be a structural member extending substantially the length of the column. The column may be formed with upper and lower cleats angled upward to engage with angled slots of the second modules. A footing may be provided for the column.

The present invention may provide advantages in reducing the need for skilled labor, scaffolding, modern tools and fasteners in the construction of structures. Indeed, need for these may be eliminated in accordance with the present invention.

#### DESCRIPTION OF THE DRAWINGS

The invention may be more fully understood from the following description of preferred embodiments thereof made with reference to the accompanying drawings in which:

FIG. 1a shows a side view of one example of a first module of the present invention used in a first preferred embodiment of the invention;

FIG. 1*b* shows a cross-section view along section line A—A of FIG. 1*a*;

FIG. 2*a* shows a side view of one example of a second module used in a first preferred embodiment of the invention;

FIG. 2*b* shows a cross section view along section line B—B of FIG. 2*a*;

FIG. 3*a* shows a detail of the bevelled cuts shown in FIG. 2, and 6 one arrangement for connection of second modules to tie rods connecting first or first and end modules in a first preferred embodiment of the invention;

FIG. 3*b* shows a front elevation of portion of a web of a first or end module;

FIG. 4*a* shows a side view of one example of an end module used in a first preferred embodiment of the invention;

FIG. 4*b* shows a cross section view along section line C—C of FIG. 4*a*;

FIG. 5*a* shows a side view of one example of an alternative first module for use in a first preferred embodiment of the invention;

FIG. 5*b* shows a cross section view along section line A—A of FIG. 5*a*;

FIG. 6*a* shows side elevation of one example of an alternative second module for use in a first preferred embodiment of the invention;

FIG. 6*b* shows a cross section view along section line B—B of FIG. 6*a*;

FIG. 7*a* shows an elevation of one example of a tie rod for use in accordance with a first preferred embodiment of the invention;

FIG. 7*b* shows a plan view of the tie rod of FIG. 7*a*;

FIG. 8*a* shows an elevation of an alternative example of a tie rod for use in accordance with the invention;

FIG. 8*b* shows a plan view of the tie rod of FIG. 8*a*;

FIG. 8*c* shows and end elevation view of the tie rod of FIGS. 8*a* and 8*b*;

FIG. 9 shows a plan view of one example of a tie rod to be used at a corner formed by two walls meeting at right angles and constructed in accordance with the method of the invention;

FIG. 10 shows a plan view of one example of a key for use at a corner in accordance with one embodiment of the present invention;

FIG. 11*a* shows plan and elevation views of one type of key which may be used in a first preferred embodiment of the method of the invention;

FIG. 11*b* shows plan and elevation views of a second type of key which may be used in a first preferred embodiment of the method of the invention;

FIG. 11*c* shows one example of a wedge which may be used in accordance with a first preferred embodiment of the method of the invention;

FIG. 11*d* shows one example of a hook bolt and washer which may be used in accordance with the method of the invention;

FIG. 12*a* shows a side elevation view of one example of a capping for a wall used in a first preferred embodiment of the invention;

FIG. 12*b* shows a section view of the capping along section line 1—1 of FIG. 12*a*;

FIG. 12*c* shows a side elevation view of a further example of a capping for a wall used in a second preferred embodiment of the present invention;

FIG. 12*d* shows a section view of the further capping along section line 2—2 of FIG. 12*c*;

FIG. 13*a* shows a plan view of one example of a wall assembled in accordance with one embodiment of the method of the invention;

FIG. 13*b* shows an elevation of the wall shown in FIG. 13*a*;

FIG. 14 shows an enlarged detail of FIG. 13*a*;

FIG. 15*a* shows a plan view of one example of an external corner formed by two walls meeting at right angles and assembled in accordance with one embodiment of the invention;

FIG. 15*b* shows a part elevation of the wall shown in FIG. 15*a*;

FIG. 16*a* shows a plan view of one example of an internal corner formed by two walls meeting at right angles and assembled in accordance with one

FIG. 16*b* shows a part elevation of the wall shown in FIG. 16*a*;

FIG. 17*a* shows a plan view of one example of a double module pier, assembled in accordance with one embodiment of the invention;

FIG. 17*b* shows a plan view of one example of a single module pier assembled in accordance with one embodiment of the invention;

FIG. 18*a* shows a plan view of one example of column assembled in accordance with one embodiment of the invention;

FIG. 18*b* shows an elevation view of FIG. 18*a*;

FIG. 19*a* shows a plan view of one example of a fence wall with single module piers, assembled in accordance with one embodiment of the method of the invention;

FIG. 19*b* shows an elevation view of the fence wall shown in FIG. 19*a*;

FIG. 20*a* shows a plan view detail of the fence wall shown in FIG. 19*a*;

FIG. 20*b* shows a cross section view along line A—A of FIGS. 19*a*, 19*b* and 20*a*;

FIG. 20*c* shows an end pier of the fence wall shown in FIGS. 19*a*, 19*b* and 20*a*;

FIG. 21*a* shows a plan view of one example of a connection bracket for connecting single and/or multiple module piers to a wall assembled in accordance with the method of the invention;

FIG. 21*b* shows a front elevation view of connection bracket shown in FIG. 21*a*;

FIG. 21*c* shows a detail of elevation at both ends of connection brackets shown in FIGS. 21*a* and 21*b*;

FIG. 21*d* shows an end elevation view of FIGS. 21*a* and 21*b*;

FIG. 22*a* shows a plan view of one example of connection bracket for connecting single module pier to a fence wall assembled in accordance with the method of the invention;

FIG. 22*b* shows a front elevation view of the bracket shown in FIG. 22*a*;

FIG. 22*c* shows a detail of elevation at one end of bracket shown in FIG. 22*a*;

FIG. 22*d* shows an end view of bracket shown in FIGS. 22*a* and 22*b*;

FIG. 23*a* shows a front elevation view of a connection bracket used in construction of a column according to a further embodiment of the invention;

FIG. 23*b* shows a plan view of the connection bracket of FIG. 23*a*;

FIG. 23*c* shows a side elevation view of the connection bracket shown in FIGS. 23*a* and 23*b*;

FIGS. 24*a-d* show plan, elevation and side views of one example of a door frame hook bracket assembly for use in accordance with one embodiment of the invention;

FIGS. 25*a-d* show plan, front, and side elevation views of one example of a first hook bracket for fixing a door frame, a window frame or another wall in accordance with one embodiment of the invention.

FIGS. 26*a-e* show plan, front and side elevation views; and inverted elevation views of one example of a second hook bracket for fixing a door or window frame in accordance with one embodiment of the invention;

FIG. 27 shows a plan, front and side elevation of a third hook bracket for, in cooperation with the hook bracket of FIGS. 25*a-d*, fixing two walls abutting together in accordance with one embodiment of the invention;

FIG. 28*a* is a front elevation of one example of a door frame for use in accordance with one embodiment of the invention;

FIG. 28*b* is a side elevation of the door frame of FIG. 17*a*;

FIG. 28*c* is a section of the door frame along section line A—A of FIG. 28*a*;

FIG. 28*d* is a section of the door frame along section line B—B of FIG. 28*a*;

FIG. 28*e* shows a view along section line C—C of FIG. 28*d* showing connection detail of the hook bracket of FIG. 26 to the door frame side of FIG. 28*a*;

FIG. 29 shows one example of assembly stages for a door or window assembled in accordance with one preferred embodiment of the invention;

FIG. 30*a* shows a front elevation of one example of a window frame for use in accordance with the method of the invention;

FIG. 30*b* shows a side elevation of the window frame of FIG. 30*a*;

FIG. 30*c* shows a view of one side of the window frame of FIGS. 30*a* and 30*b*;

FIG. 30*d* shows a view of the opposite side of the window frame of FIGS. 19*a* to 19*c*;

FIG. 30*e* shows a cross section view of the window frame along section line A—A of FIG. 30*a*;

FIG. 30*f* shows a cross section view of the window frame along section line B—B of FIG. 30*a*; and

FIG. 31*a* shows an elevation of one example of a window for use in accordance with the method of the present invention;

FIG. 31*b* shows a section of the window frame along section line A—A of FIG. 31*a*;

FIG. 31*c* shows a section of the window frame along section line B—B of FIG. 31*a*;

FIG. 31*d* shows a section of the window frame along section line C—C of FIG. 31*a*; and

FIG. 31*e* shows a section of the window frame along section line D—D of FIG. 31*a*.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The method of the invention includes the assembly of various modular components. Therefore, description is first provided of the first, second and end modules; the connec-

tion or tie means used for connecting the first and end modules; or first and first modules thus providing a supporting structure for the second modules.

#### 1. The Modules

In a first preferred embodiment of this invention, the first and second modules 10 and 20 are plain T-Cross section panels as shown in FIGS. 1 and 2. There are also provided Half T-Cross section end modules 30 in the form of panels, (or L-Cross section panels) as shown in FIG. 4. The length of these modules is generally the full height of the wall to be constructed and the widths and thicknesses of the cross sections of the same modules depend on the design of the same wall. However, an alternative construction may be envisaged in which the modules are sized only to form a portion of the height of the wall, for example above or below windows or doors.

In yet another form of this invention the first, second and end modules could be made from fiber reinforced concrete, from metal, from timber or from any other suitable material. They also could be made of composite construction whereby the flange of the T-section and the Half T-Section (L-Section) is made from one material and the web from another, e.g. concrete flange with metal web or vice versa. Fiber reinforced concrete or cement flange with metal web or vice versa. Timber flange with metal web or vice versa and so on. In all such cases the web of each module is provided with suitable anchorage to fit the connection means, modified if required, as necessary to connect the modules together to form the wall in accordance with the method of the invention.

As shown more clearly in FIGS. 13*a* and 13*b* which show the assembled wall 40, first and end modules 10 and 30 form one face 40*a* of the wall 40 being constructed. Second modules 20 form the other face 40*b* of the same wall 40. This may be an outer face of the wall 40 where such is an external wall. For an internal wall, the first and second modules 10 and 20 may be used for either face of the wall 40.

End modules 30 are generally used at each end of the wall 40 and also on each side of any opening provided in the same wall, for example, on each side of a door frame or window frame as shown in FIG. 29. They may be used elsewhere along the wall and may define sides of a wet joint in the same wall. A wet joint is a vertical joint which may be provided anywhere along the length of the wall and which may be filled with cement and sand mortar, wall plaster or other suitable materials finished flush with both faces of the wall to complete the wall. Wet joints are introduced along the length of a wall to compensate for any shortfall in the given lengths of a wall which does not correspond to a full or end module.

First, second and end modules 10, 20 and 30 may be used to form a pier or a column or may be cut into shorter lengths to be used, as a fence wall or above and below any openings provided in the same wall 40, in the same manner as full-length units. Also, first and second modules 10 and 20, modified as necessary, are used to form external and internal corners in walls meeting at right angles and at different angles and of the required length. In these cases, the modules may be molded or cut with web and flange at the required angles. For example, the webs or flanges may have an edge extending at a desired angle to the plane formed by the panel portion of the modules. Flanges of first and second modules may be molded smaller when used at right angle corners.

All modules are advantageously lightweight in construction allowing convenient handling by one or two people.

As all modules have same or similar cross-section, they may be produced from a single mold or single mold modi-

fied to suit. The cross-section described may be varied from the T-cross section provided that the modules may still be employed in accordance with the method of the invention. The First Module

Referring more particularly to the first module **10**, as shown in FIG. 1, this module is a plain concrete T-shaped cross section panel. The length of the panel is equal to the full height of the wall being constructed. The widths, and thickness of the flange and web of the panel and the overall thickness of the panel depend on the design of the same wall.

The web **12** of this first module **10** is provided, at locations along its length with small rectangular holes **13**, which pass through from one face **12a** of the web **12** to the other face **12b**. These rectangular holes **13** extend perpendicularly to the longitudinal axis of the first module **10**. The number and location of these holes **13** depends on the height of the wall being constructed and on the design loads acting on the same wall. At least two such holes **13** are required per module and locations proximate the top and bottom of the web **12** are suitable bearing in mind expected design loadings.

The main function of these small rectangular holes **13** in the web **12** of first module **10** is to provide positive connection and anchorage to the tie rod **50**, as shown in FIG. 7 or **8**, which connects first modules **10** together; or first and end modules **10** and **30** together when constructing the wall in accordance with the method of the present invention.

As shown in FIGS. 5 and 6, the webs **12** and **22** of each of the first and second modules **10** and **20** could also be provided with longitudinal recesses **16** and **28** which run the full length of the unit on both sides of the webs **12** and **22**. The small rectangular holes **13** in the webs **12** of first modules **10** and the bevelled cuts **26** in the webs **22** of second modules **20** remain the same.

#### The Second Module

Referring more particularly to the second module **20**, as shown in FIG. 2, this module is a plain concrete T-shaped cross section panel. The length of the panel is equal to the full height of the wall **40** being constructed. The width and thickness of the flange **21** and web **22** of the panel and the overall thickness of the panel depend on the design of the same wall **40**.

The second module **20** is similar to first module **10** in cross section, in length and in size. However, it has large angled slots **26** in its web **22**. The smaller rectangular holes **13** which are provided in the web **12** of first module **10** are omitted. These large angled slots are in the form of bevelled cuts **26** at predetermined angle from the horizontal, for example  $30^\circ$  or  $45^\circ$  (see FIG. 3a) and locations, for example proximate the ends of the web **22** of the module **20**. The ends **26a** of slots **26** may be rounded. This results from a possible process of fabrication where holes are first drilled through web **22** at desired locations of the slots **26**. An angled cut, at the required angle  $\alpha^\circ$ , is then made to meet the drilled hole producing the slot shape shown. A horizontal cut is made to intersect this angled cut at its opening. Angles and location of cuts are selected having regard to required strength. The same bevelled cuts **26** are intersected by a horizontal cut **27** at the face of the web **22** to form the shape of cut shown generally in FIG. 2; and in detail in FIG. 3a. The number, size and angle of these bevelled cuts **26** depend on the height of the wall **40** to be constructed and on the design loading of the same wall **40**. Two such bevelled cuts **26** located proximate the ends of the web should suffice. The width of these bevelled cuts **26** is selected to snugly fit the tie rod **50**, shown in FIG. 7 or **8**, for connecting the first and second modules **10** and **20** together.

The main function of these bevelled cuts **26** is to guide, positively anchor and fix a second module **20** to a corresponding tie portion **57** of the tie rod **50** which connects first or end modules **10** or **30** together; and first and end modules **10** and **30** together (to form the supporting structure) to become part of a wall **40**. Therefore, these, same bevelled cuts **26** form the connection portions of second modules **20** which, through cooperative engagement with the corresponding tie portion(s) **57** of connecting tie rod(s) **50**, effectively connect it to first, end or first and end modules **10** and **30** to form a wall **40** without the use of cement mortar, bolts, screws, or the like. Accordingly, the bevelled cuts **26** and horizontal slots **27** are a particularly important feature of this preferred embodiment of the invention.

Second modules **20** are also used in the construction of columns and piers in accordance with further aspects of the invention.

#### The End Module

End module **30** also takes the form of a plain concrete Half-T-Cross section panel (i.e. L-Cross-section panel) as shown in FIG. 4. The length of the panel is equal to the full height of the wall being constructed. The width and thickness of the flange **31** and web **33** of the panel and the overall thickness of the panel depend on the design of the same wall.

The external face of the web **33** of end module **30** is provided with a longitudinal recess **36**, which runs the full length of the module **30**. The width and depth of this longitudinal recess **36** is designed to suit keys and/or hook brackets, as shown in FIG. 25, allowing connection of end module **30** to other modules or fittings as described further below. Recess **36** may be omitted in half-modules as used in pier constructions as described below.

The web **33** of end module **30** is also provided along its length with the same size of small rectangular holes **32** as those provided in the web of first module **10**. Also, the same number of holes **13** provided in the first module **10** correspond to an equal number of the same holes **32** provided in end module **30**. For example, if first module **10** has three slotted holes **13** provided in its web **12** at a certain height, then three out of the larger number of slotted holes **32** provided in the web **33** of end module **30** must exactly correspond and be located at the same height and location along its web **33** as those provided in the web **12** of first module **10**.

End module **30** may be provided with more of the same small rectangular holes **32** along the length of its web **33** than first module **10**. These extra rectangular holes **32** are designed to provide anchorage and fixity for the window and door frames which may be fixed to the end module **30**. End modules **30** are located on each side of the door and window openings and may be used for the shorter cut modules which may be located below and above an opening. End modules **30** may also be located to define a wet joint along the wall. They are also used at piers along a wall where connection of two end modules **30** may form a supporting structure for second module(s) forming at least part of a pier.

The main function of these small rectangular holes **32**, which are provided in the web **33** of end module **30** is to, provide positive connection and anchorage, to the tie rod **50** which connects first and end modules **10** and **30** together. Also, these holes **32** allow connection of the door and window frames by bracket means described further below. 2. The Connection or Tie Means

The connection or tie means ties and connects the first, second and end modules **10**, **20** and **30** together in order to form a wall **40** of desired rigidity and strength. It includes, in a preferred embodiment of the invention, a tie rod; a key and wedge; a capping; hook bolt(s) and hook brackets.

The tie rod **50** may, in one embodiment shown in FIG. 7, be a short metal rod with specially designed lug (plate) **52** connected at each end. Rectangular hole **53** is formed in each lug **52** to accommodate separate wedge components **85** to anchor the tie rod to key apertures as described below. The lugs **52** may be designed to suit the shape of the webs **13**, and **33** of the first and end modules **10** and **30**. The lugs **52** may be omitted by suitable design of the tie rod **50**.

An alternative tie rod is shown in FIG. 8. This alternative includes wedges **54** designed to suit the rectangular holes or slots **72** provided in key apertures. These wedges **54**, in contrast to wedges **85** described below are incorporated in the lugs **52** of the tie rod **50**.

Referring further to FIG. 7, the tie rod **50** is also provided with two locating guides **56** along its length, which could be rods of any suitable cross section, or plates of any shape and size. Guides **56** may be welded to tie rod **50**. Further or fewer guides could be provided, for example corner tie rods **150** have two sets of guides **56** and **156** and tie rods for piers have no guides, rather guiding is achieved by the channel sections of the pier brackets as described below. The spacing "d" between these two guides **56** is designed to suit the width of the web **22** of second modules **20**. A neat fit may be desired. These guides **56** are designed to guide, locate and restrain second modules **20** into desired positions along the wall **40**, when it is anchored to the tie rod **50** which connects first modules **10** together; and/or first and end modules **10** and **30** together to form the wall **40**; or two end modules together to form a pier or column.

The guides **56** need not be located symmetrically about a centre line between the lugs **52**. Their position is selected having regard to the desired position of second modules **20** in the constructed wall **40**.

The overall length of the tie rod **50** (including the lugs **52**) is designed to suit the flange width of the modules **10** and **30** so that when connected together by the tie rod **50** the desired spacing, centre to centre, required between them is advantageously achieved.

Moreover, the same tie rod **50** may be bent and modified in length and profile as required and is also used to tie or connect together the modules which form the external and internal corners of walls meeting at different angles and the modules forming a pier or column or any other structural member.

Referring to FIG. 9, there is shown a suitable tie rod **150** for a right angle corner, each arm of which extends in a direction of one of the walls forming the corner (see FIG. **15a**). This angle may be varied of course to allow cornering at different angles than 90°.

The main function of the tie rod **50** is to tie and connect the first modules **10** together; and first and end modules **10** and **30** together to form one face of the wall or two end modules **30** together to form a pier, and to provide positive anchorage and fixity to second modules **20** which connect to the tie rod **50** to form the opposite face of the same wall **40**; or a pier or column. The tie rod **50** also transmits the horizontal and longitudinal forces acting on the same wall. Two or more such tie rods **50** may be employed in the connection of adjoining modules.

Tie rods connecting first modules may be referred to herein by notation including "50" in this description. Modified tie rods may be designated by notation including "51", for example those tie rods connecting end modules **30** or first and end modules **10** and **30**.

Keys **88** and **89**, shown in FIG. 11, perform in conjunction with wedge **85** two important functions. Firstly, they lock and fix the tie rod **50** to the first, and end modules **10** and **30** on driving wedges **85** into position.

Secondly, the keys fix window frame and/or door frame brackets to end modules **30** on driving wedges **85** into position.

Keys **88** or **89** and wedges **85** may be used in combination though key means could be designed to achieve both functions. To illustrate how the keys **88**, **89** and wedges **85** work, consider for example two vertical surfaces which need to be locked and fixed firmly together by means of the key and wedge. The two surfaces must first be provided with the same size holes to fit the key being used. The two surfaces are brought together with the holes aligned. A key is inserted through the holes of both surfaces. A wedge **85** is then driven through the rectangular hole **72** provided at the pointed end of the key **88** or **89** to secure both surfaces together. The further the wedge **85** is driven into the key hole(s) **72** the bigger the compression force applied and the tighter the two surfaces are gripped together.

The key **88** or **89** may take the form of a rectangular metal plate of width and thickness to suit and shaped as shown in FIGS. **11a** and **11b**. Keys are designed to fit the small rectangular holes **13** and **32** provided in the webs **12** and **33** of the first and end modules **10** and **30**. One end **88a** or **89a** of the key **88** or **89** may be slightly tapered or pointed to facilitate fitting it through the small rectangular holes **13**, **32** in the webs **12**, **33** of the modules **10** and **30** and the other end **81** is provided with a wide flange **82** to stop it from passing completely through the same holes.

Two types of keys may be used in accordance with the invention. One type (type "E") **88** is provided with only one rectangular hole **72** at its pointed end **88a**. A second type (type "I") **89** is provided with two rectangular holes **72** one at each end of the key.

Each of the above key types could be made in different length and profile, for connection of different modules at different locations to perform different functions. Type E keys **88** are used with end modules **30** at the end of a wall **40** or along the sides of window or door openings in order to lock and fix the door or window frame bracket to an end module. A modified key **188** with right angled key arms **187** is used at a right angle corner and at walls meeting at different angles. Arms **187** may be disposed at different angles for different angle corners and may be provided with apertures **172** to accommodate wedges **85**.

Type "I" keys **89**, used in connection of first modules **10**, could have different shapes and different lengths depending on their location along the walls being constructed, however function remains the same. Appropriate shape and length keys are selected by the builder during construction.

The keys provide positive anchorage and fixity to the tie rod **50**. The keys **88** and **89** also transmit the design longitudinal and horizontal loads from one module to the next through the tie rod **50**.

The wedge **85** is a small piece of metal plate, straight on one side and tapered on the other as shown in FIG. **11c**. The metal of the wedge **85** may be substituted by other materials. It is designed to fit the rectangular slot(s) **72** provided in the keys **88** and **89** and in the lugs **52** at each end of the tie rod **50**. It is used in conjunction with keys for locking, tying and fixing the modules together and for locking and fixing any brackets to first, second and end modules **10**, **20** and **30** by wedging action.

The cappings, shown in FIG. 12, are generally C-shaped sheet metal cappings. The width of cappings **100** and **180** is designed to suit the thickness of the wall **40** being built and its length may vary to suit the construction of the same wall **40**, the handling and transport.

Two types of capping **100** and **180** have been designed to be used in accordance with the invention, as shown in FIGS.

12a-d. The capping 100 shown in FIGS. 12c and 12d may be a plain capping which is a C-shaped sheet metal capping which has no cleats attached to its web and it may or may not have large voids 101 in its web 107. It could be used on top as well as at the bottom of the wall being built.

The capping may be a castellated and/or cleated capping 180, as shown in FIGS. 12a and 12b. This capping 180 is also a C-shaped sheet metal capping except it is provided with cleats 106 at the outside face of its web 107. These cleats 106 could be punched through the web 107 of the plain C capping 100 at the required centres and folded outwards leaving large voids in the web 107 of the C channel to form a castellated cleated capping 180. Alternatively, the cleats 106 could be welded on the outside web 107 of the capping 180 and the large voids in the web 107 punched separately or the metal C section could be manufactured with large voids 101 in its web 107 and cleats 106 welded to the web 107 to produce a castellated cleated capping. This type of capping 105 is used only at the top of the wall 40. It is designed to provide fixity to other structural members supported on the top of the same wall such as ceiling joists, roof rafters and roof beams. Holes 109 are drilled in the cleats 106 to allow connection to these structural members.

The capping 100 or 180 connects the modules 10, 20 and 30 forming the wall together at the top of the wall 40, and assists in alignment of the modules, to distribute part of the horizontal and vertical forces along the wall, to provide restraint at the bottom of the wall 40 if and when required by fixing the capping to the floor and to provide fixity at the top of the wall 40 for other structural members which bear on top of the wall such as ceiling joists, roof rafters, roof beams etc. Capping length may be the length of a flange of a first module 10, greater or less as desired.

The cappings 100 or 180 could be made from suitable materials other than metals. They may be shaped to suit columns or corners.

The cappings 100 or 180 may be connected to the wall 40 by hook bolts 121 if required due to expected loadings. Suitable hook bolts 121 are hot dipped galvanised bolts (or any other approved rust treated bolts) one end 125 of which is bent in the shape of a hook and the other end 127 of which is threaded to fit a suitable nut 131 and a rectangular washer 130, as shown in FIG. 11d.

The diameter of the hook bolts 121 vary, depending on the height of the wall 40 and the wind and other loadings acting on the same wall 40. The length of the hook bolts 121 is designed to suit the position of the nearest top tie rod 50 or 51 to which it connects. The washers 130 may take the form of a rectangular flat metal washers. The length of the washer 130 is equal to the full thickness of the wall 40 and its width and thickness are proportioned to suit the design of the bolt 121.

The capping 100 or 180 is fixed to the top of the wall 40 hooking the hook bolt 121 to the top tie rod 50a which ties the modules 10 and 30 together and bolting the rectangular washer 130 across the thickness of the wall 40 and on top of the capping 100 or 180 as shown in FIGS. 15 and 16.

#### Construction of a Wall

Description now follows of the assembly of modules, tie rods and capping to form a wall referring to FIGS. 13a, 13b and FIG. 14.

Construction of a wall 40 may start anywhere along the wall at a first module 10; or with an end module 30 forming a start or an end to the wall 40; or at a corner. For illustrative purposes, construction will be assumed to start at an end module 30. The end module 30 is stood in an upright position with its flange 31 running along the line of the wall

to be constructed. One type E key 88 is fitted to the top and one to the bottom of the end module 30 in the small rectangular holes 32 provided through its web 33. The pointed ends 88a of these keys 88 must point in the direction of the wall 40 being constructed in distinction to other keys 89, used in forming the wall 40, which face in the opposite direction. The height at which these keys 88 are fixed correspond to the height of the bevelled cuts 26 provided in the web 22 of second modules 20.

Then a first module 10 is stood next to the end module 30 with its flange 11 also extending along the same line of the wall 40 as flange 31 of end module 30. A type "I" key 89 is then to be fitted in each of the slotted holes 13 provided through its web 12. One type "I" key 88 is fitted at the top and one is fitted at the bottom of the module 10. The pointed end 89a of the key 89 faces against the direction of the wall 40 being constructed (see FIGS. 13a and 14).

Now the end and first modules 10 and 30 are ready to be connected or tied together with the modified tie rod 51, having shorter length than tie rod 50 used in connection of adjacent first modules 10, forming an assembly which is a supporting structure 200 for second modules 20. The supporting structure 200 effectively forms a hanger from which a second module 20 is "hung" to form part of the wall. It may be called a hanger unit.

Starting at the bottom, then at the top of modules 10 and 30, tie rods 51b and 51a respectively are slid between the webs 13 and 33 of the standing modules 10 and 30. Wedges 85 are then driven securely into the rectangular holes 72 provided in the keys 88 and 89 in both modules 10 and 30 and in the lugs 52 provided at each end of tie rods 51a and 51b. Once the bottom and the top tie rods 51a and 51b are anchored into position by the keys and wedges 88, 89 and 85 the two modules 10 and 30 are locked together in the longitudinal direction of the wall 40 and spaced at the required centers. The first and end modules 10 and 30 have flanges forming one face 40a of the wall 40 and, connected by the two tie rods 51a and 51b between them, form the hanger unit 200.

A second module 20 is then stood in the upright position and opposite the hanger unit 200 formed by the first and end modules 10 and 30 such that its web 22 is facing and in line with the centre line 59 of the guides 56 provided on the tie rods 51a and 51b.

The second module 20 is now lifted slightly and allowed to temporarily hang off the top tie rod 50a and between the guides 56 provided on it, by the top horizontal cut 27 provided in its web 22. The second module 20 has the bottom bevelled cut 26 in its web 22 guided between the bottom tie rod guides 57b. The second module 20 is then simply pushed gently forward against the other two standing modules 10 and 30. This will allow module 20 to drop over and engage corresponding portions 57a and 57b of the top and bottom tie rods 51a and 51b with the cooperating bevelled cuts 26 anchoring and locking it to the tie rods 50a and 50b, thus forming the opposite face 40b of the 40. Flange 21 ends overlap webs 11, 31 or 11 and 31 of first and/or end modules 10 and 30 forming supporting structure. Spaces 24 separate the flange 21 ends of adjoining second modules, and indeed first and/or end modules 10 and 30. These may be used for insertion of brackets, other fittings but may be rendered or plastered if desired. The three modules 10, 20 and 30 are thus now locked effectively together in both longitudinal and horizontal directions thus forming part of the wall 40 being constructed.

Then another first module 10 is placed in the upright position with its flange 11 along the line of the wall 40 next

to the previous first module **10**. Top and bottom keys type "I" **89** are fitted into position through the rectangular holes **13** in its web **12**, and in line and level with the previous ones. The pointed ends **89a** of the keys must be facing against the direction of the construction of the wall **40**, (i.e. facing the start of the wall). Two more tie rods **50** are inserted between the two first modules **10** and anchored into the keys **89** of this new unit and the last one thus again forming another hanger unit **201**. Another second module **20** is hung between them and anchored to the tie rods **50** and so on. The same procedure is repeated until the construction of the wall **40** is complete.

The wall capping **100** or **180** and the hook bolts **120**, if required, may also be fitted as the wall construction progresses or whenever is convenient. Depending on the height of the wall **40**, temporary propping to the wall might be necessary until the wall is made secure but scaffolding are unnecessary.

On construction of external walls, internal walls may be constructed in the same manner. Structural members located at the top of the walls are assembled on completion of wall construction.

There is now described, with reference to FIGS. **15a** and **15b**, construction of an external corner of an external wall **140** of a structure, for example a house. In this case, flanges of first modules **110** form the internal faces **140a**, **141a** of the cornering walls **140**, **141** and flanges of second modules **120** form the external faces **140b**, **141b** of the walls **140**, **141**.

Starting at the corner **190**, two first modules **110** are stood upright at right angles to each other. Their flanges **111** run along the internal face of the wall in each direction and their webs **112** face the external face **140b** of the wall **140**. Two type I keys **89** are fitted into the rectangular holes **113** at the top and bottom of each module **110**. The pointed ends **89a** of the keys **89** point towards the corner **190**.

The modules **110** may then be connected together by the corner tie rod **150** shown in FIG. **9** to form an assembly which is a supporting structure for two second modules **120a** and **120b**. Two such corner tie rods **150** are connected between the webs **112**, one at bottom, the other at top; and secured by driving wedges **85** into the apertures **172** of the tie rods **150**. The first modules **110** are tied together in the longitudinal direction of each line of the walls **140** and **141** forming the corner **190**.

Second modules **120** used at corners are similar to second modules **20** used elsewhere but do have width of their flanges **122** modified or shortened to suit the corner **190**.

Second module **120a** is more easily connected first to the supporting structure **200** and second module **120b** is connected afterwards completing the external corner **190**.

The remainder of each wall **140** and **141** is constructed in the manner above described. Another first module **10** is stood next to first module **110** with its flange **111** running along the same line of the wall. Type I keys **89** are fitted into the top and bottom rectangular holes **132** provided in its web **112**. A tie rod **50** is slid between the webs **112** of the two modules **110** at top (**50a**) and bottom (not shown) to engage with the keys **89**. Wedges **85** are driven at each end of each tie rod **50** to secure and anchor them to the keys **89** forming hanger unit **200**. Second module **20** is then connected to the same tie rods and so on until the cornering walls **140** and **141** are completed.

There is now described, with reference to FIGS. **16a** and **16b**, construction of an internal corner **290** of an external wall **240**. A first module **210a** is fitted at top and bottom rectangular holes **213** in its web with one key arm **187** of corner key **188**. The other key arm **187** of key **188** is fitted

into corresponding rectangular holes of first module **210b** stood at right angles to first module **210a**. The first modules form part of adjoining supporting structures. Both key arms **187**, which are disposed at a right angle, point away from corner **290**. The flanges **211a** and **211b** are modified or shortened to suit the corner **290**. The flanges **211a** and **211b** have the same length as flanges of second modules **120a** and **120b** forming the corner of FIG. **15**.

Then further first modules **10** are connected to the first modules **210a** and **210b** by tie rods **150** engaged with the key **188** and **89** by driving wedges **85** into position. This completes assembly of supporting structures or hanger units **200** for the second modules **220a** and **220b** which are connected, in the manner previously described, to the hanger units **200**. Second module **220a** is more easily connected first followed by second module **220b**. The corner **290** should be water-tight with no gaps allowing passage of water.

Construction of the cornering walls **240a** and **240b** continues as previously described.

Construction of Piers

There is now described, with reference to FIGS. **17a** and **17b**, the construction of a piered wall. Piers **370** may be constructed along a wall **340** in order to strengthen the wall, to carry a special load acting on the wall and to give extra lateral stability to the wall.

In accordance with this aspect of the invention, piers may be constructed anywhere along the length of a wall provided that second modules **20** and **320** of the wall and pier being constructed are directly opposite each other with their webs **22** and **322** facing each other when connected to the tie rods **50**.

Two types of pier may be constructed. A single module pier (FIG. **17b**) has width formed from one module. A multi-module pier (FIG. **17a**) has width formed from a number of modules.

Construction of a piered wall is similar to construction of two separate walls alongside each other and tying both together using the pier bracket **380** of FIG. **21**. The number of pier brackets **380** to be used to tie a pier to a wall should not be less than the number of tie rods **350** used to connect an assembly forming a hanger unit **201**. That is, where two tie rods **350** are used, two pier brackets **380** are likewise needed at top and bottom to connect the pier **370** to the remainder of wall **340**.

The pier bracket **380** comprises two channel sections **386**, which form guides for second module webs, connected by a plate or web section **390**. The ends **387** of the channel sections **386** are rounded with the walls forming the channel section **386** provided with slotted holes **382**.

One method for the construction of a single module pier **370** along a wall **340** constructed with two tie rods is as follows: as the construction of the wall **340** progresses and at the required location of the pier **370** the first tie rod **350** is inserted at the bottom between two standing first modules **310**. Wedges **85** are anchored loosely at both ends of the tie rods into the key apertures **372**.

Before the wedges **85** are securely driven into the apertures **372** a pier bracket **380** is inserted between first modules **310** with the slotted holes **382** of the bracket **380** facing downward. Spaces **314** left to allow fittings facilitate such insertion. First modules **310** may be moved forward or backward to accommodate this being only loosely connected at this time.

The slotted holes **382** are engaged onto the tie rods **350** and wedged **85** are driven in tightly to anchor the tie rod **350** to the keys **89** at each end ensuring that the pier bracket **380** is fully engaged with the tie rod **350**.



The next tie rod **350** is inserted at the top between the webs **312a** and **312b** of first modules **310a** and **310b**. This tie rod **350** is firmly anchored at each of its ends by fully driving the wedges **85** into key apertures **372** of keys **389**.

When the top tie rod **350** has been anchored, another pier bracket **380** is inserted from the top above the tie rod **350** and between the first modules **310a** and **310b**. The slotted holes **382** of this pier bracket **380** are likewise pointed downward.

The slotted holes **382** are pressed into engagement with the tie rod **350** at locations on each side of the guides **356**.

The first modules **310a** and **310b** are connected together following this step to form a supporting structure for second module **320** with pier brackets **380** in position ready for the pier **370** to be constructed.

Two end modules **330** are then stood in the upright position with their flanges **331** back to back against the flanges **311** of first modules **310a** and **310b**. Webs **333** of the end modules **330** face each other with the pier bracket **380** symmetrically between them.

Pier tie rod **351**, a modified tie rod, is then slid between the webs **333** of end modules **330** and under the pier bracket **380** to engage slotted holes **382** on each side of the guides **386**. Pier tie rod **351** is similar to tie rod **50** but has length adapted to the application. Guide rods may be omitted as channel section **386** may form a guide for web **322** of second module **320**.

Type E keys **88** are then inserted in each end module **330** to support the pier tie rod **351**. Wedges **385** are driven at each end of the pier tie rod **370** through the key apertures to secure the tie rod **351** to the keys **88**.

The same procedure is repeated at the top. On completion, two end modules **330** form a supporting structure or hanger unit for second module **320** which is connected to the structure in the manner previously described for wall **40**. Such connection should follow full engagement of slots **382** with the wall and pier tie rods **350** and **351** at top and bottom of the wall at the pier location.

A multi-module pier may be constructed by the same method of construction as previously described. In this case, a first module **317** is arranged with flange **317a** back to back to first module **310b**. This first module **317** is connected to each end module **330** forming supporting structures for each second module **320**, as shown in FIG. **17a**, in the manner familiar to the invention.

#### Construction of Columns

There is now described, referring to FIGS. **18** and **23**, the construction of load bearing columns in accordance with a still further embodiment of the present invention.

Column **700** construction involves only second modules **20a-20d**, special connection brackets and, where necessary for bearing heavy loads, structural members. The special connection brackets **400** may be used for light loading on the column of the type encountered in single storey housing projects. For heavy loadings, structural members which may, for example, be of steel or timber of rectangular or other suitable cross-section may be employed.

The bracket **400** is shown in FIG. **23** and is made of a rectangular structural hollow section **401**, with four cleats **402, 403, 404, 405** connected to it. The cleats **402-405** are in the form of plates with upstanding edges **412, 413, 414, 415** in the manner of a box section. The cleats **402-405** are connected at an angle to the horizontal medial axis of the bracket **400** which corresponds to the angle of the bevelled cuts **26** provided in the web **22** of second modules **20**. This angle may be, for example,  $45^\circ$ .

Two opposed cleats **402** and **404** connected to two opposed sides **401a** of the rectangular hollow section have

angle facing upward. Adjacent these on the remaining opposed sides **401b** are two opposed cleats **403** and **405** with angle facing downward.

The plate portions **402a, 403a, 404a** and **405a** are designed to engage with the bevelled cuts **26** provided in webs **22** of second modules **20** when assembled into a column.

If a structural member is used to carry heavier loads, the cleats **402-405** are connected directly to it at upper and lower locations but all cleats are angled upward and, conveniently, the structural member is of rectangular hollow section. In this case, cleats **402-405** also correspond with the beveled cuts **26** of second modules **20**.

The following description is directed to a column **700** construction for bearing lighter loads.

A suitable footing **790** is formed of concrete or other suitable material. Two second modules **20a** and **20b** are stood on the footing **790** with webs **22a** and **22b** opposing each other. The bevelled cuts **26** of each module **20a** and **20b** face downward so that cleats **403** and **405** of brackets **400a** and **400b** may be dropped into them at top and bottom respectively. On completion, there is formed a supporting structure for two remaining second modules **20c** and **20d** with walls **413** and **415** assisting in making a secure connection. Modules **20c** and **20d** are reversed in relation to modules **20a** and **20b** such that their bevelled cuts **26** face upward. These bevelled cuts **26** are brought into engagement with cleats **402** and **404**, walls **412** and **414** assisting in making a secure connection, after which connection the column **700** is completed.

A capping member **710** suitable for the column **700** may be fitted at the top.

#### Assembly of a Door Frame

Description now follows of connection of a door frame **500** to a wall **40** constructed in accordance with a method of the present invention and is made referent to FIGS. **24** to **26, 28** and **29**.

The door frame **500**, shown in FIG. **28**, could be made of metal, timber or any other suitable door frame material of the type used or suitable to be used in the building industry. The most commonly used standard door frames in the building industry are metal and timber door frames.

The metal door frame **500** may be pre-formed or pressed in the factory and advantageously is manufactured complete with architraves, door stops, hinges and latch striker. The width of the door frame **500** is designed to suit the width of the wall **40**; or the width of wall **40** making allowance for wall plastering thickness.

At the back faces **580** of both sides of the doorframe **500**, that is the faces adjacent to the wall **40**, the metal is folded outward away from the architraves, giving each side of the door frame **500** two vertical planes **502** running the full height of the frame **500** and facing the wall **40**. This may be conveniently seen in FIGS. **28b, 28d** and **28e**.

In accordance with a preferred embodiment, the door frame **500** may be connected to end modules **30** defining each side of a door opening by a hook bracket assembly **520** as shown in FIGS. **24** to **26**. The top of the door frame **500** is formed such as to allow any shorter first or second modules **10** or **20** above the door frame to sit flat inside the frame with the top architraves restraining these modules from any horizontal movement.

The door frame hook bracket assembly **520** may be of any kind, any shape and size suitable for fitting to end module **30** provided that the door frame sides are such that the door frame **500** can hook and fix to the wall **40** from one side. From the other side of the frame a further end module **30**

must connect to the door frame **500**. The hook bracket assembly **520** is designed to meet the design strength criteria of the wall **40** being constructed.

In a preferred embodiment of the invention, the hook bracket assembly **520** may be made of flat metal plate of width and thickness to suit the design strength of the wall **40** and doorframe **500** and includes two interlocking brackets: a first bracket **510**; and a second bracket **515** as shown in FIGS. **24**, **25** and **26**. The brackets **510** and **515** are designed to suit the type, the size and the profile of the door frame **500** used. For example, a timber door frame could have a second bracket **515** of different shape and fixity than to a steel or aluminum door frame.

The first bracket **510**, as shown in FIG. **25**, is U-shaped with width designed to fit the width of the longitudinal recess **36** provided in end module **30**. The centre of the U-shaped first bracket **500** is provided with a slotted hole **530** to allow fixity to the end module **30** by means of keys and wedges **88** and **85** as earlier described. Other connection means could be employed and end modules **30** could be provided with the first brackets **510** fixed in desired positions.

The legs **540**, which may have rounded ends, of the U-shaped first bracket **510** are provided with specially shaped slotted cuts **550** which act as hooks. These slotted cuts **550** cooperate and interlock with similar slotted cuts **517** of the second bracket **515** of the door frame hook bracket assembly **520**. It is to be noted that the slotted cuts **517** and **550** are wider at one end than another, this allows location to be made more easily prior to engagement.

FIG. **26** show these slotted cuts **517** located symmetrically about the centre line of second bracket **515**. This desirable arrangement is not limiting. Other locations could be used.

Second bracket **515** may be connected to the door frame **500** by suitable keying or securement by cooperation between slots **522** formed in arms **512** of second bracket **515** and rectangular slots **590** formed in the vertical planes **502** running the height of the door frame **500** and facing wall **40** as shown in FIGS. **28b**, **28d** and **28e**. The second bracket **515** could also be fixed to the door frame **500** in the factory or it could be fixed on site during construction.

Alternatively, if the door frame **500** is formed or pressed without the vertical planes **502**, the second bracket **515** may be fixed, by welding or otherwise, to each side of the door frame **500** at the designed location(s).

It is preferred that a number, desirably three or four, such hook bracket assemblies **520** are used on each side of the door frame **500** in order to secure it to the wall **40**. The location of the first brackets **510** on the end modules **30** must correspond with the locations of second brackets **515** along the side of the door frame **500** so that both, when engaged, can appropriately hook together to make the connection as required.

Construction of the door proceeds as follows:

Step **1**. At the door position along the wall **40**, three first brackets **510** are fixed to an end module **30** using keys **88** and wedges **85**. The legs **540** of first brackets **510** point sideways towards the door opening. The slots **550** provided in the legs **540** of the first bracket **510** face upward.

The number of the hook bracket assemblies **520** required for each side of any door frame **500** depends on the size and the height of the door. One bracket assembly **520** is required at each end of the frame and one at the middle of the frame. Also fixed to the door frame side **503**, the side which is to be fixed first to end module **30** of the erected wall, is second bracket **515** having slots **517** facing downward.

Likewise, bracket assemblies **520** are fixed on the other side of the door frame, that to be connected to end module **31**. In this case, the assembly is inverted. That is, second bracket **515** is connected to the door frame side **504** with slots **517** facing upward and first bracket **510** is connected to end module **31** so that its slots **550** face downward.

Step **2**. The door frame **500** is lifted slightly, so that second bracket **515** on the door frame **500** just clears first bracket **510** on the end module **30**. The door frame **500** is then allowed to gently drop vertically until it rests on the floor. This will automatically interlock slots **550** of first bracket **510** with slots **517** of second bracket **515** so that one side of the door frame **500** is locked and securely fixed to the wall **40**.

Step **3**. A further end module **30** is stood up vertically with the recess **316** of the web **313** facing the free standing door frame side. Three more first brackets **510** are fixed at the corresponding height as the second brackets **515** on the door frame side, but this time with the slotted hook cuts **550** of the first brackets **510** face downward. The slots **517** of second brackets **515** face upward. Each of the brackets **510** and **515** is inverted in direction to that on the other side of the door frame **500**.

Step **4**. The further end module **30** is lifted and lined symmetrically against the free standing side **504** of the door frame **500**. The end module **30** is allowed to gently drop vertically to the floor. This engages and allows the slots **550** of its first brackets **510** to interlock with the slots **517** of the second brackets **515** on the door frame **500** thus securely locking and fixing the end module **30** to the door frame **500**. From there on the construction of the wall **40** may proceed in the above described manner. The construction of the shorter modules **10** or **20** which fit above the door may be commenced at any time as the construction of these shorter units is independent of the construction of the remainder of the wall **40**.

#### Assembly of a Window Frame

Now follows a description of construction of a window in accordance with a preferred embodiment of the invention. A window **800** for use in accordance with the method of the invention includes:

- a structural window frame part **810**, shown in FIG. **19**, which is completely independent of the window **800** shown in FIG. **20**. This frame part **810** connects and fixes directly to the modules and carries all external vertical and horizontal loads acting on the window **800**. Thus, lintels above the windows may be avoided.
- a window part **820**, shown in FIGS. **19** and **20**, which has a light metal frame containing the window sashes and the window fly screen. This part fits inside the structural window frame part **810** and is secured in position from the outside by means of a clip-on metal beat **830** which forms part of the external architraves of the window frame.

The window frame **810** could be made from metal such as aluminium, and steel, timber or any other suitable material. It is connected to end modules by hook bracket assemblies similar to the door frame hook bracket assemblies **520** described above. The window frame **810** sides are provided with second brackets **515**. Alternatively, depending on the material and the into the window frame sides **812** during the manufacturing process. Slots **817** suit slots **550** of first brackets **510**. A suitable window frame **810** for the latter will have a hollow rectangular section.

These second brackets **580** or slots **817** allow the window frame **810** to be fixed on one side to the end module **30**; and,

on inversion, on the other side to end module **31** in the same manner as for the door frame **500** described above. This allows secure fixing of the window frame **810** to the wall **40** being built. The number of hook brackets required per window depends on window size.

#### Connection of Walls

In analogous manner to connection of door and window frames to the wall, internal walls or partitions may be connected to other walls or partitions of the structure with hook bracket assemblies. Thus a first wall or partition may be connected to a second wall or partition by hook bracket assemblies having cooperating portions connected to the first wall or partition along a line of desired connection and along a vertical length of one end of the second wall, or partition. Two or three such hook bracket assemblies are generally suitable to connect one wall or partition to another.

The hook bracket **1520** used, as part of the assembly, is similar in function to second hook bracket **515** described above and is shown in FIG. **27**. It comprises a flat plate bent to form a middle U-shaped section **1519** with two flanges **1518**. Flanges **1518** are provided with apertures **1530** to accommodate fasteners to secure the hook bracket **1520** to the wall along the line of connection of the wall. Slots **1517** are formed in the U-shaped section **1519** having wider portions at top than at bottom to assist in location prior to securement. They are formed with portions extending back to flange **1518** to accommodate legs **540** of first brackets **510** which extend beyond slots **550** which are accommodated in slots **517** of bracket **1520**. The first brackets **510** are connected in corresponding locations to brackets **1520** along the vertical length of the module forming the end of the second wall. Engagement of the slotted cuts **1517**, **550** of the first and second brackets connects the first and second walls together in the same manner described above for door frames and window frames.

#### Construction of a Fence Wall

Fences are designed to resist specified lateral wind loads. This can be achieved either by anchoring them into the ground, by joining them to some means which is anchored to the ground, that is, columns, which can resist lateral loads or by increasing their lateral stability by weight or by the use of piers at certain spacings along the length of the fence wall. In accordance with this aspect of the invention, lateral stability of the fence wall may be achieved by any of the above methods or any combination of them.

As with above described aspects, first, second and end modules are employed to construct a stable solid fence wall. The construction of a standard height fence wall **640** (say up to 1.8 m high) involves basically the construction of single module or multi-module piers (as above described referring to FIGS. **17a** and **17b**) depending on the wind design loads acting along the length of the fence wall. Such piers **680** could be located on one face **640a** of the fence wall **640** or on both faces **640a** and **640b**, at equal spacings or alternating spacings on each face as shown in FIG. **19a**.

At each pier center line position along the fence wall **640**, the same wall is intersected by a pier bracket **384** connecting the intermediate piers **680** to the face **640a** of the fence wall **640**.

At the location of each intermediate pier **680**, the fence wall **640** comprises two end modules **660** arranged back to back between which portion **643** of pier bracket **384** passes. Pier bracket **384** has portions cooperating with pier keys **689** used in connecting end modules **660**; and tie rod **351** which is used to connect pier end modules **630**. Such cooperation allows positive joining of piers **680** to the wall **640**. This is shown in FIG. **19a** and more clearly in FIG. **20a**.

Lateral stability of the wall **640** is achieved partly by embedding part of the length of all or some of the piers **680**, or alternate piers **680**, depending on the height of the fence wall **640**, into the natural ground and partly by the mass or weight of the wall **640** and piers **680**.

In certain instances, a column of steel, or any other suitable material, can be anchored into the ground by concrete footing along the length of the fence wall **640** at design spacings and the fence wall **640** joins and connects to it. The higher the fence wall **640**, the greater the lateral forces acting on it and the more piers are needed to be anchored into the ground to resist these forces.

Standard fence walls generally start and end with piers **688** anchored into the natural ground and have further anchored piers **680** between them.

A suitable footing **690** for the fence wall **640** is a first module **610** laid flat and level between the fence piers **680**, in suitably prepared footing trenches. The flange **611** faces upward and the web **612** downward so that it can form a solid hard surface under the modules **610**, **620** and **630** forming the wall **640**. This can be achieved since forces on the wall due to settlement are practically non-existent.

Starting from one end **641** of the fence wall **640**, a trench is dug and prepared in the ground to the lines and levels required. The depth of the trench could be any practical depth provided that the fence wall **640** is allowed an embedment of not less than 100 mm below ground.

The length of the first modules **610** which are designated to be used as footing modules **690** depends on the design spacing between piers **680**. It is advantageous to keep their length to a practical minimum bearing in mind the handling and the weight of the modules. The length of a footing module **690** preferably spans the pier to pier spacing. Thus, the vertically standing first module **610** at each end of the wall **640c** between the piers **680** centerlines, that is the first module **610** which is connected by means of tie rod **650a** to the end module **660** to form a hanger for second module **620** has maximum support beneath it without interfering with the embedment of the fence pier **680** modules as shown in FIGS. **19a** and **20a**.

At a distance at least equal to the width of the pier **680** being constructed from the starting line, the first module **610** designated for the footing **690** is laid at the lines and levels required. Web **612** faces downward. Proper embedment in the natural ground is ensured and the soil around it is compacted. This footing **690** can now act as a gauge from which to measure the depth of embedment of the pier **680** modules specified for the particular height of the wall **640**.

The fence wall **640** commences with the single module pier **680** shown in FIG. **20a** which may be constructed in a manner similar to that described for FIG. **17** but note use of end modules **630a** and **630b** which are brought into alignment with webs **633a** and **633b** spaced, rather than back to back. These end modules **630a** and **630b** are located in a hole prepared for them. A further end module **30** is arranged back to back with end module **630b**. Keys **88** are inserted into end module **630a** holes **632a** facing in the direction of fence wall **640** at top and bottom. Keys **89** facing against the direction of the wall, and having suitable length for the job, are inserted at top and bottom through holes **32** and **632b**.

Tie rod **651b** is then inserted at the bottom between the two standing end modules **630a** and **630b**. Wedges **85** are anchored loosely at both ends of the tie rod **651** in key apertures **672** such that pier bracket **380** may be inserted between the end modules **630a** and **630b** with slotted holes **382** facing downward. Spaces **614** facilitate such insertion which takes place by moving the pier bracket **380** down-

wardly relative to the extending webs **633a** and **633b** into required position. End modules **630a** and **630b** may be moved forward or backward to accommodate bracket location being only loosely connected at this time.

Slotted holes **382** of pier bracket **385** are engaged onto the tie rod **651** and wedges **85** are driven in tightly to anchor the tie rod **651** to the keys **88** and **89** such that pier bracket **380** is fully engaged with the tie rod **651**.

The operation is repeated at the top and, on completion, construction of a single module pier **680** may be completed as described in respect of FIG. 17 (noting that end modules here form the supporting structure at this portion of the wall rather than first modules). Second modules **20** are connected and these, the modules **630a**, **630b** and pier modules **630** are embedded in the ground at a depth specified by the designer, say 600 mm below natural ground level (NGL).

From end module **30**, construction of wall **640** continues in the manner above described up to the next pier location where an end module **660** is used to terminate the wall segment **695**.

A further end module **660** is then arranged back to back with end module **660**, again located in a hole corresponding with the location of the intermediate pier **685**, and pier keys **689** are inserted, at top and bottom (designated by "a" and "b" respectively in the drawings), between the two modules **660** with pier brackets **384** connected to the pier keys **689**. Pier bracket **384** is shown in FIG. 22, and is similar to bracket **380** with the exception that it has a channel section **386** only at one end for a single-sided pier; it would have two channel sections **386** for a double sided pier. Keys **689** extend through apertures **662** in end modules **660** (recesses omitted); and also through slot **388** in plate section **390** of pier bracket **384** making connection between pier brackets **384** and keys **689**.

Channel section **386** has width greater than the distance between pier tie rod **685** guides (if any are provided) and its ends **387** are rounded. It is provided with slots **389** on each side of the channel section **386** to engage with the tie rod **351** connecting the end modules forming the supporting structure for second module **620** which completes the pier. This tie rod **351** is shorter in length than tie rod **50**. Thus, this pier bracket **384** is positioned, with slots **389** facing upward, prior to construction of the pier **680**, which occurs in the manner previously described. Embedment completes the job.

The construction of wall **640** and piers **680** from that point is as above described, for construction of a pier **370**, except that the tie rod **351** will be brought into engagement with slots **382** of pier bracket **385** from above and not below.

Construction of the fence wall **640** can be advantageously achieved when working from one end of the wall **640** to the other constructing the wall **640** and pier **680** together as the construction progresses rather than building the wall first and the piers after.

Suitable capping **100** or **180** may be employed during construction or after the fence wall **640** is complete. Corners may be formed in a fence wall in the manner as above described.

#### Modifications and Variations

Modifications and variations may be made to the invention as described herein by those skilled in the art. Such modifications and variations are within the scope of the present invention. For example, even though the modules are described as having a plain concrete panel portion, this portion could be fabricated as desired without modification of the invention. For example, different shaped or different colored modules could be employed in accordance with the invention.

In yet another form of the invention the small rectangular holes **13**, **32** in the webs of first and end modules **10** and **30** and the large angled slotted cuts **26**, **27** in the web **22** of second module **20** could be replaced by brackets or mouldings of any suitable material such as steel, aluminum, etc. These brackets or mouldings could be cast into or surface mounted and fixed to the sides of the web or to the flange of the section and the connection means could be modified to suit them with or without the use of the keys and wedges which are part of the connection means. The necessary positive vertical, longitudinal and horizontal anchorage to the modified connection means connecting the modules together is still to be achieved. Moreover, the same brackets or mouldings could run the full length of the module(s) or could be of shorter lengths located at designated locations along the length of the web of the module(s).

Further, the tie rod could be modified at its ends to suit the connection means provided for connection of first and end, end and end or first and first modules.

The claims defining the invention are as follows:

1. A wall, comprising first, second, and end modules, and a connection means for tying adjoining modules together in tension, wherein the first module comprises a web and a flange, wherein said web is formed with rectangular holes for accommodating the connection means connecting the module with a further module to form a supporting structure for second modules.

2. A wall, comprising first, second, and end modules, and a connection means for tying adjoining modules together in tension, wherein the first module comprises a web and a flange forming part of a face of the wall, wherein said web is formed with rectangular holes for accommodating the connection means connecting the module with a further module to form a supporting structure for second modules.

3. A wall, comprising first, second, and end modules, and a connection means for tying adjoining modules together in tension, wherein the end module comprises a web and a flange, wherein said web is provided with a recess having rectangular holes for accommodating key means for connection of said end module to a further module forming a support structure for second modules.

4. A kit for use in construction of a wall, comprising first, second and end modules, or frames, window frames, capping members and first, second, third and/or fourth connection means, wherein the first module comprises a web and a flange forming part of a face of the wall, wherein said web is formed with rectangular holes for accommodating the connection means connecting the module with a further module to form a supporting structure for second modules.

5. The kit as set forth in claim 4, wherein the end module comprises a web and a flange, wherein said web is provided with a recess having rectangular holes for accommodating key means for connection of said end module to a further module forming a support structure for second modules.

6. A method of construction of a wall from first, second and end modules, the method comprising:

aligning a first or end module and one of: a first and an end module in a desired alignment;

connecting the two modules together with at least one first connection means, having a tie portion generally extending in the direction of alignment, to form a supporting structure for at least one second module; and

connecting a second module to the supporting structure by cooperation of a connection portion of said second module with a corresponding portion of said supporting structure to form at least a portion of the wall, wherein the portion of the wall is held in tension.

25

7. A method of construction of a wall from first, second and end modules each having a portion forming one part of the face of the wall, the method comprising:

aligning a first or end module and one of: a first and an end module in a desired alignment;

connecting the two modules together with at least one first connection means, having a tie portion generally extending in the direction of alignment, to form a supporting structure for at least one second module; and

connecting a second module to the supporting structure by cooperation of a connection portion of said second module with a corresponding portion of said supporting structure to form at least a portion of the wall, wherein the portion of the wall is held in tension.

8. The method of claim 7, wherein said second module is connected to the supporting structure by cooperative engagement of said second module connection portion with a corresponding portion of said tie portion of the supporting structure connection means.

9. The method of claim 7, wherein adjoining first, end, or first and end modules are connected together by a plurality of first connection means spaced along vertical lengths of the adjoining modules providing a plurality of corresponding tie portions for engaging cooperation with plural connection portions of the second module allowing connection to the supporting structure.

10. The method of claim 7, wherein said first connection means includes a guide means for locating said second modules in desired spaced relation to the supporting structure.

26

11. The method of claim 10, wherein said guide means forms part of said tie portion and said corresponding tie portion has length substantially equal in width to said second module web.

12. The method claim 7, wherein the wall comprises an L-section end module defining an end to a wall, said end module being connected to a further first module by connection means.

13. The method of claim 12, wherein the end module is provided with a second connection means for connection to one side of a door frame or window frame.

14. The method of claim 13, wherein said door or window frame includes, on another side, second connection means for connection to a further end module.

15. The method of claim 7, wherein, at a corner, first modules are aligned at the angle of the corner and connected together by a third connection means including a key or tie portion angled at the angle of the corner to form a supporting structure for second modules to complete the corner.

16. The method of claim 7, wherein, at a corner, modules of adjoining supporting structures are aligned at the angle of the corner and connected together by a third connection means including key or tie portions shaped to suit the corner.

17. A structure including a wall constructed in accordance with claim 7.

18. A structure as claimed in claim 17 being a fence.

\* \* \* \* \*