

ARCH 1230
BUILDING TECHNOLOGY II

Professor Friedman

FALL 2012



SUBJECT

Building Technology II

Foundations Part II

DATE

FALL 2012

PROFESSOR

Friedman

FOUNDATIONS

Professor Friedman

spread the load into the earth

arch 1230



this week

objective:

overview of the function of foundations and the process of designing foundations



- * foundation requirements
- * deep foundations
- * caissons
- * piles
- * pile caps
- * grade beams
- * underpinning
- * designing foundations

FOUNDATIONS

Professor Friedman

Foundation Requirements

ARCH 1230

FOUNDATIONS MUST MEET FOLLOWING THREE GENERAL REQUIREMENTS:

1. MUST BE SAFE AGAINST STRUCTURAL FAILURE THAT COULD RESULT IN COLLAPSE
2. MUST NOT SETTLE DURING LIFE OF BUILDING IN SUCH A WAY THAT WOULD DAMAGE STRUCTURE OR IMPAIR FUNCTION
3. MUST BE FEASIBLE, ECONOMICAL, & PRACTICAL (WITH NO IMPACT ON NEIGHBORS)



FOUNDATIONS

Professor Friedman

Deep Foundations


ARCH 1230

DEEP FOUNDATIONS ARE REQUIRED WHERE:

- THE DEPTH OF ADEQUATE BEARING MATERIALS IS TOO GREAT FOR SHALLOW FOUNDATIONS (IMPRACTICAL, TOO \$\$\$\$)

AND/OR

- THE PRIMARY AVAILABLE BEARING MATERIAL REQUIRES FRICTION RESISTANCE WITH THE FOUNDATION SYSTEM



FOUNDATIONS

Professor Friedman

Deep Foundations


ARCH 1230

DEEP FOUNDATIONS:

TRANSMIT BUILDING LOADS
TO DEEPER, MORE
COMPETENT SOILS
THE TWO TYPES OF DEEP
FOUNDATIONS ARE:

- END BEARING
- BEARING THROUGH FRICTION

NOTE: SOME DEEP
FOUNDATIONS FUNCTION
IN BOTH MODES.



FOUNDATIONS


Professor Friedman

Deep Foundations

ARCH 1230

CAISSON:

Is similar to a column footing in that it **spreads the load** from a column **over a large enough area of soil** that the allowable stress in the soil is not exceeded.




FOUNDATIONS

professor Friedman


Caissons

ARCH 1230


①




②



③



④



Constructed by drilling a hole, placing a steel support cage, and filling with concrete...

FOUNDATIONS

Professor Friedman

Caissons

ARCH 1230



CAISSONS:

A CONCRETE CYLINDER
POURED INTO A DRILLED
HOLE.



FOUNDATIONS

Professor Friedman

Caissons

ARCH 1230

Steel Casings may be used to temporarily support the side walls of the hole.

[Can be removed after concrete placed.]



FOUNDATIONS

Professor Friedman

Caissons

ARCH 1230

Reinforcement is usually only required at the top to tie the caisson to the structure it supports



FOUNDATIONS



professor Friedman

Caissons

ARCH 1230

Caissons (sometimes called piers) can sometimes be **as small as 12 to 18 inches** in diameter.

Most of the time, are much larger, **up to 8 ft in diameter and carry 3,500 tons or more.**



FOUNDATIONS

professor Friedman

Caissons

ARCH 1230

Auger drills generally used to bore deep into the earth and remove the soil.



FOUNDATIONS

professor Friedman

Caissons

ARCH 1230

Small portable drills




FOUNDATIONS

professor Friedman

Caissons

ARCH 1230

Larger telescoping drills



FOUNDATIONS

professor Friedman

Caissons



ARCH 1230

Belling Bucket

Used to significantly **increase the bearing capacity** of bored piles/ caissons by enlarging the base area.

Cutting arms are opened mechanically.

-**Practical in stable conditions** (a cohesive soil such as clay) that can retain its shape until concrete is poured.



FOUNDATIONS

professor Friedman

Caissons

ARCH 1230

Steel Casings

Lowered around the drill as it progresses to **support the soil** around the hole. **Later removed** after concrete is poured.



FOUNDATIONS

professor Friedman

Caissons

ARCH 1230

Chicago Spire by Santiago Calatrava
(under construction)

2,000 feet tall, 150 stories (proposed)

34 caisson holes dug 120' underground



FOUNDATIONS

professor Friedman

Tower columns supported by Caissons



FOUNDATIONS


professor Friedman

Caissons

ARCH 1230

Caissons in water:

Over the years, builders have used caissons to provide support for bridges, deep water drilling, docks, etc...





FOUNDATIONS

professor Friedman

Caissons

ARCH 1230



FOUNDATIONS

professor Friedman


Caissons

ARCH 1230

Brooklyn Bridge:

Towers built upon caissons **up to 78' underwater.**

A large wooden box was built offsite, shipped, and dropped into the water. Water was pumped out and the **ground/mud was removed by hand.**





FOUNDATIONS

professor Friedman

Caissons

ARCH 1230

Conditions were rough, air was pressurized and if workers came up to the surface too quickly, they would get the bends (called Caisson disease).



FOUNDATIONS

Professor Friedman


Piles

ARCH 1230



PILES:

a structural element that is **forcibly driven** into the earth (as a nail is driven into wood).



FOUNDATIONS

Professor Friedman

Piles

ARCH 1230

PILES:

Generally used in conditions where caissons are impractical.

-Non-cohesive Soil

-Subsurface water conditions

-Excessive depth of bearing strata



FOUNDATIONS

Professor Friedman

Piles

ARCH 1230

Materials Used:

- WOOD
- STEEL
- PRE CAST CONCRETE (PICTURED)

Material must be suitable to subsurface conditions




FOUNDATIONS

Professor Friedman

Piles

ARCH 1230

PILES ARE DRIVEN INTO THE EARTH OFTEN CLOSELY SPACED TO DEVELOP ENOUGH BEARING CAPACITY FOR THE WALL OR PIER IT WILL SUPPORT.



FOUNDATIONS

Professor Friedman

Piles

ARCH 1230

Wood/ Timber Piles

- Have been used for **over 2000 years**.
- Some Timber piles beneath bridges in Europe are known to have remained **in continuous service for more than 1,000 years**.

Negatives

- Suitable only for relatively **light loads** (40 tons each).
- Must be **preservative-treated** when they will extend above the water table.
- Limited in length** to the effective height of the tree from which they are cut (**45' – 65'**) since they cannot be spliced together.



FOUNDATIONS


Professor Friedman

Piles

ARCH 1230



WOOD PILES WORK WELL WHEN CONSISTENTLY KEPT UNDER WATER



FOUNDATIONS

Professor Friedman

Piles

ARCH 1230

Steel Piles

- May be “H” shaped sections or pipes.
- H shaped piles are **heavy**, wide-flange sections varying in size from 8-14” wide.
- Can carry **loads of 50- 200 tons each**.
- May be **up to 150’ long**.
- To produce super lengths, sections **can be welded together** as they are being driven.



FOUNDATIONS


Professor Friedman

Piles

ARCH 1230

H-Steel Piles

- H-piles have a maximum length of 250'
- Can hold up to 200 tons each



FOUNDATIONS

Professor Friedman

Piles

ARCH 1230

Steel Pipe Piles

- Are later **filled with concrete**.
- May be smooth walled or corrugated, round or fluted.
- Can carry up to 250 tons.
- Pipes with **open ends** can be driven up to about 80'.
- Pipes with **closed ends** can be driven up to 120'.



FOUNDATIONS

Professor Friedman

Piles

ARCH 1230

Precast Piles

- Are either solid concrete or open cylinders that are later filled solid.
- May be square, round, or octagonal in cross section.
- All are **reinforced** and most are **pre-stressed**.
- Sizes can vary from 10- 54 inches wide.
- Solid rectangular piles w/ simple reinforcement can be **up to 80' long and hold 100 tons**.
- Pre-stressed Cylinder piles can be extended **up to 200' long and hold 500 tons**.




FOUNDATIONS

Professor Friedman

Piles

ARCH 1230



FOUNDATIONS

Professor Friedman

Piles

ARCH 1230



FOUNDATIONS

Professor Friedman

Piles

ARCH 1230

Piles are driven with heavy hammers in large machines called **Pile Drivers**. Drop hammers are simply raised and dropped on a pile by **force of gravity**. Today, they also use steam pressure, compressed air, vibratory hammers, and diesel driven hammers.






FOUNDATIONS

Professor Friedman

Piles

ARCH 1230



FOUNDATIONS


Professor Friedman

Piles

ARCH 1230



DENSE PILES
CAPPED BY A
MASSIVE MATT
SLAB SUPPORT
THE BURJ KHALIFA





FOUNDATIONS

Professor Friedman

Pile Caps

ARCH 1230



PILE CAPS:

CAPS JOIN SEPARATE PILES AT THE TOP TO TRANSFER AND DISTRIBUTE THE LOAD OF THE STRUCTURE ABOVE DOWN THROUGH THE INDIVIDUAL PILES.

FOUNDATIONS

Professor Friedman

Pile Caps

ARCH 1230



Pile Cap Casting



FOUNDATIONS

Professor Friedman

Grade Beams

ARCH 1230



GRADE BEAMS:

GRADE BEAMS ARE SUPPORTED BY CAISSONS OR PILES EVEN THOUGH THEY SIT ON THE EARTH AT GRADE.




FOUNDATIONS

Professor Friedman

Grade Beams

ARCH 1230



GRADE BEAMS:

REINFORCEMENT OF GRADE BEAMS IS SIMILAR TO ORDINARY CONCRETE BEAMS IN A FRAMED STRUCTURE.

FOUNDATIONS

Professor Friedman

Grade Beams

ARCH 1230



spread footings supporting freestanding columns and piers.

A continuous footing is a reinforced concrete footing extended to support a row of columns.

A grade beam is a reinforced concrete beam supporting a bearing wall at or near ground level and transferring the load to isolated footings, piers, or piles.







FOUNDATIONS

Professor Friedman

Underpinning

ARCH 1230

UNDERPINNING:



FOUNDATIONS

Professor Friedman

Underpinning

ARCH 1230



**UNDERPINNING:
REQUIRED WHEN:**

1. EXISTING FOUNDATION IS SETTLING IN DANGEROUS MANNER.
2. NEIGHBORING PROJECT REQUIRES DEEPER FOUNDATIONS DIRECTLY ADJACENT TO EXISTING FOUNDATIONS

FOUNDATIONS

Professor Friedman

Underpinning

ARCH 1230

UNDERPINNING PROCESS:

1. DIG NARROW
TRENCHES WIDELY
SPACED APART
UNDER EXISTING
FOUNDATIONS

2. POUR NEW
CONCRETE
WALL/FOOTING INTO
TRENCH

3. REPEAT FOR SOIL
AREA BETWEEN FIRST
TRENCHES





FOUNDATIONS

Professor Friedman

Underpinning

ARCH 1230






FOUNDATIONS

Professor Friedman

Underpinning

ARCH 1230




FOUNDATIONS

Professor Friedman

Underpinning

ARCH 1230



FOUNDATIONS

Professor Friedman

Designing Foundations

ARCH 1230



DESIGN THRESHOLDS TO CONSIDER:

- WATER TABLE DEPTH
- SITE BOUNDARIES AND NEIGHBORING STRUCTURES
- INCREASED BUILDING LOADS ON FOUNDATIONS (DUE TO HEIGHT)
- LOCATION AND QUALITY OF BEARING MATERIALS UNDER THE SITE

wrap up

FOUNDATION DESIGN AND SELECTION IS A CRITICAL ACTIVITY IN PROJECTS THAT MUST OCCUR AT THE EARLY STRATEGIC LEVELS TO TEST THE VIABILITY OF THE PROJECT



- ✿ deep foundations can solve many challenging site conditions, even for super large/tall buildings and structures
- ✿ shallow foundations are preferred as there is less risk and expense
- ✿ underpinning is a common exercise in urban environments where adjacencies are unavoidable.